Webinar

ENGIE Journey to qualified AM manufacturer

Ensuring and validating selective laser process stability for qualification purposes

Energifosk– 23 September 2020

Steve NARDONE
3dprinting.laborelec@engie.com

Additive Manufacturing @ ENGIE



ENGIE Laborelec
In a nutshell

- ENGIE Laborelec is a leading **expertise** and **research** center in **electrical power technology**.
- Founded in 1962, the company has **over 55 years** experience in the power sector.
- ENGIE Laborelec is a **cooperative company** with ENGIE and independent grid operators as shareholders.
- Our competencies cover the **entire electricity value chain**: generation, transmission & distribution, RES, storage, usage of the energy for the industry and other end-users.
- We put a strong focus on the **energy transition** and the 3D's : **decentralization**, **decarbonization** and **digitalization**.
- We offer **specialized services**, R&D and **global solutions** in each of these domains, to companies in **all parts of the world**.

This webinar deals exclusively with the Laser Powder Bed Fusion process

Local fusion of successive metal powder layers using a high energy laser.





Simple facts

Production of 10mm-cube using 50µm-layer thickness requires:

- *200 meters of scanned lines !*
- *200 layers !*
- *Fast and local welding process with high heating/cooling cycles*

Additive Manufacturing as key enabler for operational excellence
Launch of ENGIE AM Expertise Centre in late 2015

- Fe-, Ni-, Al-based AM powders (Ti)



Laboratories
> Materials laboratories
> Non-destructive testing (inspection & qualification)
> AM Powder lab

Materials Technology
> QA/QC of inspection campaigns
> Multidisciplinary projects for thermal/nuclear power plants
> Maintenance plan optimisation and revision

Foster industrialization
> Tackle obsolescence issues
> Functionality-driven approach
> Validation & Implementation of high-end applications with high qualification standards

Certification Project
> Technological bricks: feedstock / Process / AM Material Performance
> Materials certificates 3.1 & 3.2
> Proactive approach before release of future EN 13445 Part 14

Key milestones in high-end applications @ ENGIE

Commissioning 2nd machine

Commissioning 3rd machine & Powder Lab

Redesign & Validation of radio-frequency antenna



Radio-frequency design by ENGIE

1st AM valve body (non-safety classified pressure retaining part) installed in nuclear power station

Nuclear

Nuclear

NUCOBAM:
Nuclear components based on Additiive Manufacturing

2015 | 2016 | 2017 | 2018 | 2019

Commissioning 1st machine

1st Qualification of static part & Field Testing in ENGIE CCGT

Flow Swirler for condenser air extraction pump, obsolete part

1st AM part for robot inspection in nuclear primary circuit

Nuclear

Production & delivery of 12 parts from 10 days to 49 hours

Installation of pressure regulation valve part in ENGIE CCGT

AM Facility Qualification by Lloyd's Register

CERTIFIED
ADDITIVE MANUFACTURING FACILITY QUALIFICATION

Powder Lab, Facility and produced material

Additive Manufacturing Product Quality
High-Level Overview



Process Reproducibility
- From machine to machine (same SLM brand)
- From machine to machine (different SLM brand)

Process Repeatability
- Consistent product quality from build job to build job
- Powder management, storage and reuse

Process Stability
- Consistent product quality throughout the build height
- Consistent product quality on the entire build plate

Process Qualification
- Process parameters optimization
- Sensitivity analysis
- Transferability from coupons to industrial part

ENGIE Qualification Approach for Laser Powder Bed Fusion Process



Assumptions for this Webinar

- Optimized laser process parameters already implemented during fabrication

Microstructure ✓

Relative density ✓

Key mechanical properties ✓



Challenges for production of high-end components and large productions runs



Ensuring process stability, quality & reproducibility over the long term for large production runs:

- **Large components**
- **Heavily-loaded build platform**

SIM **FATAM Project** https://www.sim-flanders.be/project/fatam-icon

Challenges for production of high-end components and large productions runs

What can go wrong along the whole value chain ?



What can go wrong along the whole value chain ?

Ensuring process stability, quality & reproducibility over the long term for large production runs :

- Influence of powder batch
- Powder storage & recycling
- Influence of build location
- Influence of build height
- Transferability from coupons to industrial part
- From build job to build job



Material Feedstock for Laser Powder Bed Fusion
Standardization & acceptance criteria

ISO/ASTM 52904-19
Additive Manufacturing – Process Characteristics and Performance: Practice for Metal Powder Bed Fusion Process to Meet Critical Applications

ASTM F3049-14
Standard Guide for Characterizing Properties of Metal Powders Used for Additive Manufacturing Processes

...

ASTM F2924-14
Standard Specification for AM Ti6Al4V with L-PBF

ASTM F3055-14a
Standard Specification for AM Ni Alloy UNS N07718 with L-PBF

ASTM F3184-16
Standard Specification for AM Stainless Steel UNS S31603 with L-PBF

...

ASTM WK62190
AM Feedstock materials Technical specifications on metal powder

But also AMS, AWS, MPFI…

AMS7024
IN718 L-PBF Material Specification

MPIF Standard 28
Method for Determination of Apparent Density of Non-Free-Flowing Metal Powders Using the Carney Apparatus

...

No quantitative acceptance criteria in ASTM standards for L-PBF powder feedstock, except chemical composition

Material Feedstock for Laser Powder Bed Fusion

Standardization & acceptance criteria



Sample Thief



Particle Morphology by Scanning Electron Microscopy

Hall flow, Carney flow and apparent density

Sample Divider

Particle Size Distribution by Laser Diffraction

Mechanical Sieving



Semi-quantitative chemical analysis by Scanning Electron Microscopy

Archimedes density testing

Metal Powder Characterization based on ASTM F3049-14





Semi-automatized tapped density method producing compaction curve as a function of number of taps for a SLM metal powder



Automated measurements of dynamic angle of repose, providing cohesive index and flowing angles for different shearing stresses

Rheometer, shear cell, wall friction

New Metal Powder Characterization Methods

Material Feedstock for Laser Powder Bed Fusion
Standardization & acceptance criteria





In-house database results from operation

- Powder storage (moisture) & traceability
- Batch-to-batch evaluation
- Batch life assessment (recyclability)

GOAL: Correlate AM Powder batch features with processability & AM Material Performance

Formulation of Acceptance Criteria / Quality Indicators / Process Window for L-PBF Powders

What can go wrong along the whole value chain ?

Influence of build location & build height





Large quality discrepancy for heavy-loaded platform without careful machine fine-tuning, even with optimal laser process parameters

Process Stability

Challenge: Homogeneous properties over the platform !



Large quality discrepancy for heavy-loaded platform without careful machine fine-tuning, even with optimal laser process parameters









Impact testing
136 J vs. 16 J



Process Stability

Challenge: Homogeneous properties over the platform !



Charpy V-notch toughness values over the build platform using optimized laser process parameters

	87	70	61	66	32
	54	74	49	75	47
	79	76	69	54	61
	73	77	89	47	35
	73	33	52	60	45
76	71	85	78	49	
65	65	92	64	39	
61	82	56	35	42	
58	47	50	25	27	
40	49	33	23	24	

Charpy V-notch toughness in Joule

Process Stability over build height & Process Transferability

Full height samples

Process Stability

- Consistent product quality throughout the build height

	107	108	104	109	108
	110	109	103	115	128
	104	111	104	135	140
	100	102	114	133	76
	113	106	87	121	55
112	111	109	112	118	
107	106	97	118	99	
111	118	112	142	85	
106	108	111	114	132	
104	102	110	116	130	



Big blocks

Process Qualification

- Transferability from coupons to industrial part



	yield strength (MPa)	tensile strength (MPa)	elongation (%)	reduction of area (%)
average	434	571	45.8	59.9
stdev	18	26	6.5	11.1

Process Stability over build height & Process Transferability
Microstructure

Before gas flow upgrade



After gas flow upgrade



After gas flow upgrade and corresponding parameter optimisation, the visible melt pools after etching seem to be less pronounced and more homogeneous in size

ENGIE Certification Project

Successful ENGIE Facility and Powder Lab Certification by Lloyd's Register on 10.09.2019

- Technological bricks:
  - Feedstock
  - Process
  - AM Material Performance
- Material certificates 3.1 & 3.2
- Proactive approach before release of future EN 13445-14

Relative Archimedes Density – Laborelec Procedure LBE04113339

	Average	Standard deviation	Comments
Results	99,43%	0,13%	8 measurements of 15mmx15mmx15mm cubes from qualification platform

Tensile properties

		Condition	Yield Strength 0,2%	Ultimate Tensile Strength	Elongation at break A5	Reduction of Area	Comments
ASTM F3184-16	*Min.*	*Solution annealed*	*205 MPa*	*515 MPa*	*30%*	*30%*	*In all build directions*
Results – XY build direction		Solution annealed	379 ± 8 MPa	614 ± 3 MPa	48 ± 2 %	60 ± 3 %	Based on 5 specimens for each build direction, as per ASTM E23 with Ø6mm
Results – 45° build direction			382± 3 MPa	606 ± 3 MPa	52 ± 2 %	63 ± 3 %	
Results – Z build direction			370± 7 MPa	566 ± 9 MPa	57 ± 3 %	65 ± 3 %	

Hardness

		Condition	Measurement	Comments
ASTM F3184-16		*Not mentioned*		
ASTM A240/A240M–06b	*Max,*	*Solution annealed*	*217 HB*	
Results		Solution annealed	185 ± 8 HV0,5	*16 measurements per cube on 2 cubes*

Charpy V-notch impact testing

	Condition	Charpy Impact Energy	Lateral expansion	Comments
ASTM F3184-16	*Not mentioned*			
Results – XY build direction	Solution annealed	122J / 130J / 132J	1,78mm / 1,82mm / 1,88mm	Based on 3 specimens for each build direction, as per ASTM E23

ENGIE Certification Project

- **Our Main Goal**
  - — Achieving ENGIE AM Facility Qualification & Material Certification
  - — Material Certificate linking Powder Batch, Machine/Process & Formed Material

- Delivery of material certificate 3.1 or 3.2 for 316L material under Lloyd's Register label



Certification of stainless steel 316L powder feedstock & our Laborelec Powder Lab

Validation of SLM500 equipment at ENGIE Fabricom Zwijndrecht

Certification of produced stainless steel (mechanical performance)

Lloyd's Register

Additive Manufacturing Product Quality and Control

Off-line / non-destructive



- Material properties determine inspectability for UT and EC
  - New manufacturing technology leads to unique challenges and material properties
  - Codes and regulations require inspection of critical components
  - Benchmark AM material against industry-standard materials (forging and casting)

Industry-standard material



AM material

Fabrication of standardized blocks with reference defects



Ultrasound testing

Eddy current testing



Calculate material properties



Benchmark against industry standard

Young modulus
Signal to noise
Absorption
Sound velocity
Anisotropy
Electrical conductivity

Implementation of qualification approach to tackle ENGIE obsolescence challenges



Reverse Engineering incorporating Metal Additive Manufacturing





HEAT TREATMENT CERTIFICATE

Customer	Element Materials Technology
Project	JOB500 320C
Ordernumber	27005-01
Ordernumber SH	19-44117
Material	
Certificate nr.	19-030





Redaction of Test Specs & Obsolescence Dossier

Post-processing

Destructive Testing on Sacrificial Valve

Day 1

Day 12

Generation of 3D Model

Manufacturing Plan & Printing

Functional Testing on Industrial Valve



CERTIFIED ADDITIVE MANUFACTURING FACILITY QUALIFICATION









ENGIE Laborelec

Reverse Engineering incorporating Metal Additive Manufacturing

Any Questions ?